

SBE 650 (600671000) Impact Drill
Cardboard box

Order no. 600671000
EAN 4007430283726



Product may differ from Image

- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Thumbwheel for Speed Preselection
- Forward and reverse rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck

Technical data

Characteristics

| | |
|-------------------------------------|----------------|
| Rated input power | 650 W |
| Output power | 320 W |
| Maximum torque | 9 Nm |
| Drill-Ø masonry | 16 mm |
| Drill-Ø concrete | 14 mm |
| Drill Ø steel | 13 mm |
| Drill-Ø soft wood | 30 mm |
| No-load speed | 0 - 2800 rpm |
| Revolutions at rated load | 1500 rpm |
| Maximum impact rate | 44800 bpm |
| Gears | 1 |
| Chuck capacity | 1.5 - 13 mm |
| Collar diameter | 43 mm |
| Drill spindle with hexagonal recess | 6.35 mm |
| Drill spindle thread | 1/2 " - 20 UNF |
| Chuck clamping type | Geared Chucks |
| Weight (without power cable) | 1.8 kg |
| Cable length | 2.5 m |

Vibration

| | |
|------------------------------|-----------------------|
| Drilling in metal | 5.8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Impact drilling concrete | 24.4 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 91 dB(A) |
| Sound power level (LwA) | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Geared Chucks
Chuck Keys
Side handle
Drilling depth guide