0 601 227 1K1 – GSB 13 RE

| Material number | 0 601 227 1K1 |
|-----------------|---------------|
| EAN | 3165140692106 |
| Carrying case | \checkmark |



Technical data

Technical data

| Rated input power | 650 W |
|------------------------------|---|
| No-load speed, 1st gear | 0 – 3,150 rpm |
| Weight | 2 kg |
| Chuck capacity, min./max. | 1.5 – 13 mm |
| Tool dimensions (width) | 70 mm |
| Tool dimensions (length) | 262 mm |
| Tool dimensions (height) | 190 mm |
| Impact rate at no-load speed | 0 – 47,000 bpm |
| Noise level | The A-rated noise level of the power tool is typically as follows: Sound pressure level dB(A); Sound power level dB (A). Uncertainty K= dB. |

Drilling range

| Drilling diameter in concrete | 13 mm |
|-------------------------------|-------|
| Drilling diameter in wood | 20 mm |
| Drilling diameter in steel | 10 mm |

Segment

| Segments | Construction Metalworking Wood Heavy Duty Range |
|-----------------|--|
| Mailing segment | Wood |





Sales information

Positioning

A breakthrough that sets new standards, increased performance, better efficiency

User benefit

- Robust pot gear housing and clamp shell motor housing for tough jobsite conditions
- Powerful 650 W motor to suit versatile professional needs
- Compact ergonomic design for fatigue-free usage

